

Magocard Specifications Sheet - Enduro Printer

Specification	Details
Single/Double-sided	The Enduro is a single-sided printer which can be easily field upgraded to double-sided by means of a simple drop-in upgrade. The Enduro Duo is pre-configured as a double-sided printer.
Card Security	The user has the option to print a HoloKote® security watermark across the card surface. When used with HoloPatch® cards, one area of the HoloKote watermark is highlighted as a high visibility security seal. A choice of 4 fixed HoloKote patterns are selectable from the printer driver.
Warranty	Two years limited depot warranty (North America and EU only). Elsewhere 1 year limited warranty.
Printer Interfaces	USB rev1.1 (USB 2.0 compatible).
Software Drivers	Windows 2000, 2003 Server user-mode, XP and Vista drivers all supplied with printer.
Card Capacity	100-card feeder, 30-card stacker.
Weight	Thermal transfer and dye sublimation on wax
Power Source	External power "brick" for 90-265V 40-60Hz (autoranging)
Dimensions	6.9in wide x 7.8in high x 8.3 in deep. (175mm x 200mm x 211mm)
Weight	5.5kg (12 lbs).
Power Source	External power supply 100-240V 50-60Hz autoranging.
Dimensions	453mm L x 206mm W x 233mm H (17.8" L x 8.1" W x 9.2" H) including hopper and stacker.
Environment	Sheltered Office environment 10°C to 30°C (50°F to 85°F).
Print Speed	Colour 35 seconds each side. Mono 7 seconds.