

MagiCard Specifications Sheet - Tango 2e Printer

Specification	Details
Card Security	HoloKote anti-copying watermark across entire face of card.
Warranty	Three years UltraCoverPlus warranty which includes full printhead coverage and free loaner service - North America and EU only. Elsewhere 12 months limited warranty.
Printer Interfaces	USB, Ethernet and Parallel interfaces all fitted as standard.
Software Drivers	Windows 2000, 2003 Server user-mode, and XP drivers all supplied with printer.
Card Types	PVC ISO CR80 sized cards. Magnetic stripe, contactless (proximity), smart, adhesive backed and HoloPatch cards.
Card Thickness	0.020" to 0.063" (0.51mm to 1.6mm).
Card Capacity	100 cards feed hopper, 50 cards output stacker
Power Source	Internal power supply 90-265V 47-63Hz autoranging.
Print Speed	Color 22 seconds a side. Mono 6 seconds.
Cleaning	Using externally fed T-card plus replaceable cleaning roller.
Printing Technology	Thermal transfer and dye sublimation on wax
Weight	18.3lbs (8.3kg).
Environment	Sheltered Office environment 50°F to 85°F (10°C to 30°C).
Dimensions	7.6"width x 9.15" height x 18.58" length (193.5 mm width x 232.5 mm height x 471.1 mm length) including hopper and stacker.