

Magicard Specifications Sheet - Tango 2+L Printer

Specification	Details
Operation	Single and double-sided printing and lamination. Integrated card flipper turns cards over to enable double-sided printing and lamination.
Card Security	Standard and Custom Holographic Laminate films. HoloKote anti-copying watermark prints across entire face of card. The HoloKote watermark can be customized by using an optional Custom Key.
Printer Security	Locking card hopper, card stacker, card reject tray and lamination film spools.
Warranty	In North America, EU and other selected countries, the Tango +L comes with three years FREE UltraCoverPlus warranty which includes full printhead cover and free loaner service. Elsewhere 12 months limited warranty.
Printer Interfaces	USB, Parallel, and Ethernet interfaces all fitted as standard.
Software Drivers	Windows 2000, 2003 Server user-mode, XP drivers all supplied with printer.
Card Capacity	100 cards feed hopper, 50 cards output stacker.
Card Thickness	0.03" (0.76mm).
Printing Technology	Thermal transfer and dye sublimation on wax.
Weight	44lbs (20 kg)
Dimensions	27.5" long x 12" wide x 10" high including hopper & stacker. 700mm long x 300mm wide x 260mm high.
Environment	Sheltered Office environment 50°F to 85°F (10°C to 30°C).
Print Speed	Print & laminate card (single-sided) :
	between 36 & 55 secs depending on settings.
	Print & laminate card (double-sided) :
	between 82 & 120 secs depending on settings.